

motorsport range CAR8949Y/ZG

6-piston radial mount caliper

Part numbers and handing

Disc Thickness	Position	Ø27 / 31.8 / 38.1 pistons
32-36mm	LH trailing	CAR8949Y27SSLT
	RH trailing	CAR8949Y27SSRT
	LH leading	CAR8949Y27SSL
	RH leading	CAR8949Y27SSRL



Replacement parts

Item	Ø27 / 31.8 / 38.1 pistons
Seal Kit, axle set	CSK273238E751
Pistons, STAINLESS STEEL (each)	PSS2733X650 PSS3233X650 PSS3833X650
AKB Springs (each)	SSC3435X609 (x2) SSC3435X616 (x2) SSC3435X623 (x2)
Wear Plates (each)	ASC4489X556L ASC4489X556R
Bridge Pipe	PSC4489X558L PSC4489X558R
Bleed Screw (each)	FSB0080X008

Applications

General Race use, GT, Endurance.

Key features and benefits

- Billet aerospace grade aluminium alloy provides high strength and light weight.
- Differential piston diameters that minimise pad taper wear.
- Stainless steel pistons as standard.
- 2kg anti-knock back springs.
- Hard stainless steel wear plates.
- Hard stainless steel wear plates.
- Bolted pad retainer to increase stiffness, remove retainer to change pads.

Specifications

- Disc diameter range ø355 - 390mm.
- Disc thickness range 34 - 36mm.
- Dry weight 3.1kg excluding pads.
- Alcon pad reference: 4489, 18mm thick, 152mm long, 54mm deep, area 156cm² per caliper.

Installation dimensions

